



# LITOCLEAN

## ACID CLEANER FOR FLOOR AND WALL TILES

### DESCRIPTION

Concentrated organic acid based cleaner in powder. The product has a similar stain-removing capacity to that of strong acids (muriatic, hydrochloric, sulphuric) but without releasing toxic or noxious fumes.

### PACKAGING

5 kg bucket – boxes of 4 pcs.  
1 kg bucket – boxes of 24 pcs

### FIELDS OF APPLICATION

Suitable for removing the following from ceramic floor and wall tiles in interiors and exteriors:

- Stain of cement and lime;
- Cementitious adhesive or grout residues, even if coloured;
- Efflorescence in grout joints;

Also suitable for removing efflorescence and saltpetre from cementitious plaster and concrete.

### PRELIMINARY CHECKS AND SURFACE PREPARATION

Make sure that the surface to be treated is resistant to acids. If in doubt, carry out preliminary tests. Protect all surrounding materials that may be damaged by splashes of acid. Porous surfaces such

as Tuscan terracotta, cementitious plaster and concrete must be soaked to saturation with water before treatment.

### APPLICATION

Wet the surface to be treated with clean water, filling cementitious grout joints to saturation. Sprinkle the product uniformly over the surface and leave it to act for about 5 minutes. Clean the surface using a float with felt pads or an abrasive sponge to remove incrustations. Remove the acid solution from the floor using a sponge or rubber rake and rinse with plenty of clean water. If there are persistent incrustations or stains, repeat the operation. In the case of wall tiles, dissolve the product in water at a concentration of about 10% before using.

### CAUTIONS

Do not use to clean consisting of marble, travertine, reconstituted stone, limestone, or cement agglomerate.

Do not use on ceramic tiles that are not resistant to acids. If in doubt, carry out preliminary tests.

Use suitable personal protection equipment such as gloves and glasses (see safety information).

Do not use for applications not stated on this technical sheet.

### INFORMAZIONI SULLA SICUREZZA

Consult the Material Safety Data Sheet, available on request.

PRODUCT FOR PROFESSIONAL USE.

### IDENTIFICATION DATA

Appearance	White powder
Active substance	100%
Customs code	2811 1900
Shelf life	24 months in original packaging in dry place

### APPLICATION DATA

Application temperature	From +5°C to +40°C
Surface treatment time	About 5 minutes
Consumption	1 kg per 6 – 10 m <sup>2</sup>

Although the information in this technical sheet is source of our best experience, it is merely indicative.

Each specific case must be subjected to practical preliminary tests by the user who undertakes the responsibility for the final work result.

Sheet n. 306

Revision n. 3

Date: March 2012

### LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy  
Tel. +39 0522 622811 Fax +39 0522 620150  
www.litokol.it email: info@litokol.it

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =