



# LITOLUX

## HIGH- RESISTANT POLYURETHANE SHINY FINISHING WAX

### DESCRIPTION

LITOLUX is a ready-to-use polyurethane resin-wax emulsion. Its viscosity makes it suitable for vertical applications. It protects the surfaces from felt-tipped pen marks, dust, dirt and stains in general. It is highly resistant to walk-on traffic and gives the surface extra shine.

In addition, it facilitates the routine maintenance of the surface, thanks to its stain resistant properties. Easy to clean, using neutral detergents. The product is only suitable for interior surfaces.

### FIELDS OF APPLICATION

The product is very versatile and can be used for several purposes, for example:

- Protective treatment for Starlike® Decor based membrane, cementitious plaster, stone, natural and semi polished porcelain, tiles, opaque resin-bound material and fired bricks.
- Anti-dust treatment of cementitious screeds, industrial polished quartz surfaces, Litoliv S40 ECO, Litoliv Extra 15 or Litoplan Rapid based cementitious levellers.

### APPLICATION

The surface must be clean, dry and free from wax or dirt. Shake well before use.

Apply LITOLUX evenly and in a thin layer with a short-hair roller directly onto the surface in order to obtain a good level of protection and a glossy looking finish. We recommend that you do not apply too much product and that you allow at least 6 hours for the product to dry completely before you walk on the surface.

Usually, a single application of the product is sufficient. For porous materials, you can apply two layers in order to obtain a high degree of protection. The second layer must be applied only after the first one is completely dry (approx 4-5 hours).

The tools used to apply LITOLUX can be cleaned with water.

### CLEANING AND MAINTENANCE

For ordinary cleaning of the surface, use neutral detergents

### WARNINGS

- Shake the product before use
- Do not apply in temperatures below +10°C
- Use only on interior surfaces
- Do not use in saunas, Turkish baths and in case of high temperature and high humidity levels

### PACKAGING

1 litre bottle - 12 pieces box



---

**IDENTIFICATION DATA**

Appearance	Lactescent liquid
Colour	White
Odour	Unique to product
Custom code	3814 00 90
pH	7-8
Specific weight (T=+20°C)	1.035
Biodegradability	Not subject to law n.136
Shelf life	Shelf life: 24 months in original sealed packaging in a cool dry place. Susceptible to frost damage.

---

**APPLICATION DATA**

Application temperature	From +10°C to +30°C
Waiting time between first and second layer:	Approx 4 hours
Walk on time	Approx 6 hours
Consumption	15-18 m <sup>2</sup> /litre

**INFORMATION ON SAFETY**

Refer to the product's safety sheets available upon request.  
PRODUCT FOR PROFESSIONAL USE.

---

Although the information provided on this technical sheet is accurate to the best of our knowledge and experience, it is intended purely as a guideline. The user must carry out preliminary practical tests for each specific job and is solely responsible for the final result.

---

**Sheet N°525**

---

**Rev. n. 1**

---

**Date: November 2011**

---

**LITOKOL S.p.A.**

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy  
Tel. +39 0522 622811 Fax +39 0522 620150  
www.litokol.it email: info@litokol.it

COMPANY WITH  
QUALITY SYSTEM  
CERTIFIED BY DNV GL  
= ISO 9001 =

[www.litokol.it](http://www.litokol.it)