



LITOSTICK X35

HOT MELT GLUE STICKS FOR CERAMIC SAMPLES.

DESCRIPTION

Yellow hot melt glue sticks.

PACKAGING

5 kg cardboard boxes - 600 kg standard pallet

FIELDS OF APPLICATION

Used for the gluing of ceramic tile samples and show rooms. Depending on its high adhesive power, the X35 Litostick is specifically recommended for the application of non-absorbent materials such as: single-fired tiles, clinker and porcelain tiles.

APPLICATION

By means of the electric gun, extrude the hot product and apply it to points on the back of the tile, possibly in line with the feet.

Immediately apply the tile by pressing for a few seconds in order to further increase the adhesive capacity of the product. The product will dry within a few minutes and the parts will be secured.

WARNINGS

Optimise the gluing the tiles by using the product together with the vinyl adhesive PANNOFIX X30. The sticks allow for an immediate bond, whereas, PANNOFIX X30 takes much longer to dry and exceptional sealing is obtained even in contact with heat sources. Do not use the product for applications not stated on this technical sheet.

INFORMATION ON SAFETY

Refer to the product's safety sheets available upon request.
PRODUCT FOR PROFESSIONAL USE

IDENTIFICATION DATA

Colour	Yellow
Stick diameter	12 mm
Stick length	120 mm
Specific weight	0.930
Melting point	180-190°C
Open time	30 seconds
Preservation time	Unlimited inside the original packaging, in a dry place

Although the information in this technical chart is source of our best experience, it is merely indicative. Each specific case must be subjected to practical preliminary tests by the user who undertakes the responsibility for the final work result.

Sheet No. 511

Revision No. 1

Date: May 2014

LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy
Tel. +39 0522 622811 Fax +39 0522 620150
www.litokol.it email: info@litokol.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV
= ISO 9001 =