



LITOCARE MATT

PROTECTION WITH MATT COLOUR-ENHANCING EFFECT TO INTENSIFY THE TONES OF CERAMIC OR NATURAL STONE SURFACES AND FOR EPOXY AND CEMENTITIOUS GROUTING.



DESCRIPTION

Litocare Matt is a solvent-based, stain-resistant and dirt-proof protective impregnator with matt finish, used as a colour enhancer on ceramic or natural stone floor and wall coverings and to restore the colour of epoxy and cement grouting affected by efflorescence.

Materials treated with Litocare Matt are protected against oil, grease, dirt, liquids, etc.. The product is UV-resistant and thus suitable for use on both interior and exterior dry surfaces.

This treatment facilitates routine maintenance, reducing surface friction and inhibiting the penetration of dirt.

FIELDS OF APPLICATION

Suitable for the treatment of both medium-high absorbency and compact surfaces such as natural stone (marble and quartz), also with antique finish, pebbles, polished and smooth surfaces, polished porcelain stone, natural stone, quartz and marble agglomerate, floor and wall joints made with epoxy or cement grouting.

The product dries after just a few hours and guarantees long-lasting performance without developing a film on the surface.

APPLICATION

Apply a thin and consistent film of pure product on a dry and clean surface using a brush, roller, airless sprayer or fleece.

After application, wait approximately 10 minutes before removing any excess product left on the surface using a traditional single brush and white non-abrasive pad or absorbent cloth.

After removing the excess product, wait at least 6 hours before opening up the treated area to traffic.

WARNINGS

- It is important to apply the recommended quantities and carefully remove any excess product within the indicated timeframes to prevent greasiness. Always perform a test first to assess the result.
- Apply the product to perfectly clean and dry surfaces only.
- Do not apply the product to wet or heated surfaces.
- Do not wash the surface within the first 24 hours of applying the treatment. Wait until 48 hours have passed, giving the product time to firmly adhere to the surface in order to ensure longer-lasting performance.
- Do not use the product for applications not specifically stated in this data sheet.
- In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and then dispose of in a suitable container.



IDENTIFICATION DATA

Appearance	Clear liquid
Colour	Colourless
Odour	Organic solvent
Flammable	Yes
Customs code	3824 90 97
Specific gravity	800 ± 10 g/l
Flash point (ASTM D 56)	+30°C open cup
Preservation time	24 months in original packaging away from sources of heat in a well-ventilated and dry environment.

APPLICATION DATA

Allowed temperatures of application	From +5°C to +35°C
Period of surface treatment	Approx. 10 minutes
Consumption	15-20 m ² /l
Packaging	1l metal bottles

SAFETY INFORMATION

Consult the Material Safety Data Sheet, available on request.

PRODUCT FOR PROFESSIONAL USE

Although the information provided in this technical data sheet is accurate to the best of our knowledge and experience, it is intended purely as a guideline.
The user must carry out preliminary practical tests for each specific job and is solely responsible for the final result.

Data sheet no. 400

Rev. no. 0

Date: March 2016

LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy
Tel. +39 0522 622811 Fax +39 0522 620150
www.litokol.it email: info@litokol.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

www.litokol.it