



LITOCARE STONE GLOSSY

ANTI-STAIN GLOSS EFFECT PRIMER FOR NATURAL STONE WITH NON-GLOSSY FINISHING, TERRACOTTA AND MEDIUM-HIGH ABSORBENT MATERIAL



DESCRIPTION

Litocare Stone Glossy is a stain-resistant and dirt-proof protective impregnator with glossy finish for the treatment of medium-high absorbency surfaces. It creates a warm, wet effect, features excellent dirt-proof and stain-resistant properties and offers surfaces a semi-glossy appearance. This treatment facilitates routine maintenance, reducing surface friction and inhibiting the penetration of dirt.

FIELDS OF APPLICATION

Product recommended for natural stones (marble, granite, pebbles etc.) with non-glossy finishes, terracotta and medium-high absorbency materials.

APPLICATION

Apply a thin and consistent film of pure product on a dry and clean surface using a brush, roller or fleece. After application, wait approximately 5-10 minutes depending on the absorbency of the material, then spread the excess product evenly and leave to dry. After removing the excess product, wait at least 6 hours before opening up the treated area to traffic. Particularly in the case of more compact surfaces, the product tends to create a semi-glossy film that can be brushed once dry using a white non-abrasive pad to enhance shine.

WARNINGS

- It is important to apply the recommended quantities and carefully remove any excess product within the indicated timeframes to prevent greasiness. Always perform a test first to assess the result.
- Apply the product to perfectly clean and dry surfaces only.
- Do not apply the product to wet or heated surfaces.
- Do not wash the surface within the first 24 hours of applying the treatment. Wait until 48 hours have passed, giving the product time to firmly adhere to the surface in order to ensure longer-lasting performance.
- Do not use the product for applications not specifically stated in this data sheet.
- In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and then dispose of in a suitable container.



IDENTIFICATION DATA

Appearance	Clear liquid
Colour	Colourless
Odour	Organic solvent
Flammable	Yes
Customs code	3824 90 97
Specific gravity	840 ± 10 g/l
Flash point (ASTM D 56)	+30°C open cup
Preservation time	24 months in original packaging away from sources of heat in a well-ventilated and dry environment.

APPLICATION DATA

Allowed temperatures of application	From +5°C to +35°C
Period of surface treatment	Approx. 5-10 minutes
Consumption	15-20 m ² /l
Packaging	1 litre metal bottles

SAFETY INFORMATION

Consult the Material Safety Data Sheet, available on request.

PRODUCT FOR PROFESSIONAL USE

Although the information provided in this technical data sheet is accurate to the best of our knowledge and experience, it is intended purely as a guideline.
The user must carry out preliminary practical tests for each specific job and is solely responsible for the final result.

Data sheet no. 401

Rev. no. 0

Date: March 2016

LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy
Tel. +39 0522 622811 Fax +39 0522 620150
www.litokol.it email: info@litokol.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =

www.litokol.it