




LITOSTONE PROTECTOR

ANTI-STAIN WATER AND OIL REPELLENT PRIMER FOR MARBLE AND GRANITE



DESCRIPTION

Litostone Protector is a solvent-based, stain-resistant impregnator for the treatment of marble and granite. It offers stand-out and long-lasting protection without altering the natural colour of materials, preventing staining agents such as red wine, oil, ink, coffee etc. from penetrating the pores of the material, thus allowing spillages to be promptly removed. It can also be used as a pre-treatment before grouting.

The product is suitable for use on all types of natural stone with medium-low absorbency such as marble and granite.

FIELDS OF APPLICATION

Suitable for the stain-resistant treatment of marble and granite, natural stone, recomposed marble or granite, natural materials with medium-low absorbency.

APPLICATION

Apply the pure product evenly onto a clean and dry surface using a brush, roller, airless sprayer or fleece, levelling out any uneven applications. Leave the product to penetrate for approximately 10 minutes before removing any excess product, which must be meticulously removed in order to restore dryness to the surface and eliminate any residue. Use absorbent cloths and cotton materials for the removal process.

Always wait 4-6 hours before allowing the surface to be walked on.

WARNINGS

- It is important to apply the recommended quantities and carefully remove any surface excess within the indicated timeframes to prevent greasiness. Always perform a test first to assess the result.
- Apply the product to perfectly clean and dry surfaces only.
- Do not apply the product to wet or heated surfaces.
- If used as a pre-treatment, wait at least 2/4 hours after application before proceeding to grout.
- Do not use the product for applications not specifically stated in this data sheet.
- In the case of accidental leaks, soak up the product using an absorbent material (paper, sawdust, vermiculite, etc.) and then dispose of in a suitable container.



IDENTIFICATION DATA

Appearance	Clear liquid
Colour	Colourless
Odour	Organic solvent
Flammable	Yes
Customs code	3824 90 97
Specific gravity	800 ± 10 g/l
Flash point (ASTM D 56)	+23°C open cup
Preservation time	36 months in original packaging away from sources of heat in a well-ventilated and dry environment.

APPLICATION DATA

Allowed temperatures of application	From +5°C to +35°C
Period of surface treatment	Approx. 10 minutes
Consumption	15-20 m ² /l
Packaging	1 litre metal bottles

SAFETY INFORMATION

Consult the Material Safety Data Sheet, available on request.

PRODUCT FOR PROFESSIONAL USE

Although the information provided on this technical sheet is accurate to the best of our knowledge and experience, it is intended purely as a guideline.
The user must carry out preliminary practical tests for each specific job and is solely responsible for the final result.

Data sheet no. 405

Rev. no. 0

Date: March 2016

LITOKOL S.p.A.

Via G. Falcone, 13/1 42048 Rubiera (RE) Italy
Tel. +39 0522 622811 Fax +39 0522 620150
www.litokol.it email: info@litokol.it

COMPANY WITH
QUALITY SYSTEM
CERTIFIED BY DNV GL
= ISO 9001 =